

Pavilion Floors Brings You the Next Generation of Floor Preparation

With EKO-SAFE500™ leveler there is little need for surface prep. Your floor covering goes down faster saving you money and time and is environmentally safe

WHY PAVILION STANDS BEHIND EKO-SAFE™

For years we searched for a time-saving, cost-effective floor-prep product that also met our clients' health and environmental concerns. EKO-SAFE™ met those needs and we haven't found a product that can come close.

THE ADVANTAGE OF USING EKO-SAFE™

EKO-SAFE™ green-friendly products can be installed directly over most substrates, including gypsum-based surfaces, as long as they have a tensile bond strength of 72 psi. These revolutionary products can also be installed directly over all grade levels of concrete, including relatively fresh concrete, old cutback adhesive residue, flooring adhesive residues and painted surfaces without the need for scarifying or shotblasting of the surfaces.

EKO-SAFE™ FEATURES

- No shotblasting or scarifying required
- Install over all grade levels of concrete
- Install directly over adhesive residue
- Eliminate the need for expensive moisture barriers
- 80% less shrinkage compared to modified Portland cement-based products
- Creates the strongest bonds available
- Contains no harmful latex or silica
- Mold, mildew and bacteria resistant
- Applied using traditional methods
- Compatible with all adhesives and setting materials
- Competitively priced



Pavilion Floors has the expertise and experience that you need for the installation of EKO-SAFE™.

Our installers are CEIP Certified and have been thoroughly trained in the use of this technology.



TRUE GREEN. EKO-SAFE™ products do not contain any latex, which can cause allergic reactions, or dangerous silica. They are also naturally resistant to mold, mildew and bacteria growth making them the very best choice for green buildings.



PavilionSM

CaAl2O3

STRATUM

LABORATORIES

**A Leader in
Calcium Aluminate
Technology**

Our Featured Product



EKO-SAFE500™ floor leveling underlayment offers a premium quality Calcium Aluminate cement-based, pourable or pumpable floor leveling product. It is designed for use over

concrete, VCT, VAT, vinyl, ceramic, terrazzo, epoxy, sound/solid gypsum underlayments, most sound reduction mats, Urethane coatings, and quarry tile. Its proprietary formulation allows floor coverings like ceramic tile and natural stone to be installed after 3 to 4 hours. Floor covering such as carpet, vinyl sheet goods, vinyl composition tile (VCT), cork, homogeneous PVC, rubber and glue-down engineered wood can be installed 16 hours after application depending on thickness and drying conditions. Specialty adhesives such as moisture cured Urethanes and epoxies will require 24 to 48 hours depending on climate conditions.

STAR Certified Installers and a Guarantee



Our professional installers must be certified before we let them install EKO-SAFE™ products at your job site. In fact, Stratum Laboratories™ doesn't want every contractor to buy their products. They just distribute to the installers who care about the outcome and who will stand behind their work. Stratum works closely with our Stratum **Star Certified™** installers to ensure quality workmanship. We care about the entire process and stand behind our products and our installers. Stratum will even provide a written limited warranty to back up their product performance.

Who We Are

Pavilion Floors, Inc. is a unique, **INSTALL** Qualified, commercial contract flooring company. We are experts in the selection, supply and installation of a full range of floor coverings. This range includes all styles and constructions of carpet, VCT, wood, ceramic and rubber. With the selection of state-of-the-art products, we are able to offer a variety of unique solutions to the most complex installation issues. We are also proud of our floor covering asset management program – it is unrivaled in the industry and we would be happy to give you the details.

Sincerity and plain dealing distinguish us.



PavilionSM

90 Commerce Way
Woburn, Massachusetts 01801
Ph 781.933.8500
Fx 781.932.8844
Visit our website at: www.pavilionfloors.com

